


系列表 Series List

>>>导电性高分子固态铝电解电容器 (Polymer Aluminum Solid Capacitors)

Type	Series	Features	Temperature (°C)	Voltage (V.DC)	Capacitance (μF)	Load Life (Hrs)
引线型 Radial Type 	PZ	+105°C,Low,ESR +105°C,低阻抗	-55~+105	6.3~100	4.7-5600	2000
	PF	Low ESR and long Life +105°C,低阻抗,长寿命	-55~+105	6.3~100	4.7-5600	5000
	PT	High Temperature +125°C,高耐温	-55~+125	6.3~100	4.7-5600	2000
	PK ^{NEW}	High Temperature +135°C,高耐温	-55~+135	6.3-25	10-1800	1000
	RL	+105°C,Standard +105°C,标准品	-55~+105	6.3~100	4.7-5600	2000

系列表 Series List

>>>垂直贴片型铝电解电容器 Surface Mount Aluminum Electrolytic Capacitors

Type	Series	Features	Temperature (°C)	Voltage (V.DC)	Capacitance (μF)	Load Life (Hrs)
垂直贴片型 V-CHIP Type 	RVT	+105°C,Standard +105°C,标准品	-40~+105	6.3~100	1-3300	2000
	RVE	+105°C,Low ESR +105°C,低阻抗	-55~+105	6.3~50	4.7-1000	2000~3000
	RVZ	+105°C,Low ESR,Long Life +105°C,低阻抗,长寿命	-55~+105	6.3~50	4.7-1000	5000
	RVL	+105°C,Long Life +105°C,长寿命	-55~+105	6.3~100	4.7-1000	10000
垂直贴片套管型 V-CHIP Sleeve Type  	M5 ^{NEW}	+105°C,Miniture,Sleeve 小型化,5.7mm 高,套管型	-40~+105	6.3-450	1-680	3000
	M7 ^{NEW}	+105°C,Miniture,Sleeve 小型化,7.7mm 高,套管型	-40~+105	6.3-450	1-1200	5000
	MRR	+105°C,Long life +105°C,长寿命	-40~+105	160-450	1-22	6000
	MRT	+105°C,Long life +105°C,长寿命	-40~+105	160-450	1-22	8000~10000
	MJ ^{NEW}	High Temperature +130°C +130°C,高耐温,长寿命	-40~+130	6.3~450	1-3300	2000~3000
	MM ^{NEW}	High Temperature +130°C +130°C,高耐温,超长寿命	-40~+130	6.3~450	1-3300	4000~5000

系列表 Series List

>>>小型铝电解电容器 Miniture Aluminum Electrolytic Capacitors



Type	Series	Features	Temperature (°C)	Voltage (V.DC)	Capacitance (μF)	Load Life (Hrs)
低阻抗品 Low Impedance 特别适用于各类开关电源及 LED 驱动照明输出滤波	TC	Ultra Low impedance +105,极低阻抗品	-40~+105	6.3~25	100~4700	2000
	TF	“GBL” system,No water GBL,无水系,宽温度	-55~+105	6.3~63	10~10000	2000~8000
	TM	+105°C,Low ESR, +105,高频低阻抗	-40~+105	6.3~450	1~6800	2000~4000
	TP	+105°C,Low Impedance Long Life Assurance 低阻抗,长寿命品	-40~+105	6.3~120	1~6800	6000
	TS	Special Low Impedance Long Life Assurance 超低阻抗,长寿命品	-40~+105	6.3~120	22~6800	6000
	TY	+105°C,Low Impedance Long Life Assurance 低阻抗,超长寿命品	-40~+105	6.3~120	1~6800	10000
	TT	Special Low Impedance Long Life Assurance 超低阻抗,超长寿命品	-40~+105	6.3~120	1~6800	8000~12000
	TZ ^{NEW}	+105°C,Low Impedance Long Life Assurance 低阻抗,超长寿命品	-40~+105	6.3~120	1~6800	12000~15000
	TH ^{NEW}	High Temperature +125°C +125°C,高温度,长寿命	-40~+125	10~120	1~4700	2000~5000
	TJ	High Temperature +130°C +130°C,高温度,长寿命	-40~+130	10~120	1~4700	2000~5000
高保障、长寿命 High Reliability Type And Long Life 特别适用于 LED 驱动照明输入或输出滤波	RR	Long Life assurance +105°C,长寿命,小体积	-40~+105	160~500	1~220	6000
	RS	Long Life assurance +105°C,长寿命,小体积	-40~+105	160~500	1~220	8000
	RT	Long Life assurance +105°C,长寿命,小体积	-40~+105	160~500	1~220	10000
	RV	Long Life assurance +105°C,超长寿命	-40~+105	160~450	1~47	12000~20000
	RW	Long Life assurance +105°C,超长寿命	-40~+105	160~450	1~47	20000~30000
高耐高温对策品 High Temperature 特别适用于 LED 驱动照明及车载系统	RH	High Temperature +125°C +125°C,高耐温	-40~+125	160~450	1~220	2000~5000
	RJ	High Temperature +130°C +130°C,高耐温,长寿命	-40~+130	160~450	1~220	2000~3000
	RM	High Temperature +130°C +130°C,高耐温,超长寿命	-40~+130	160~450	1~220	4000~5000
	RO	High Temperature +150°C +150°C,超高耐温	-40~+150	10~450	1~1000	1000

系列表 Series List

>>>小型铝电解电容器 Miniture Aluminum Electrolytic Capacitors



Type	Series	Features	Temperature (°C)	Voltage (V.DC)	Capacitance (µF)	Load Life (Hrs)
标准型 General Purpose	RB	+85°C,Standard +85°C,标准品	-40~+85	6.3~500	0.1~22000	2000
	RK	+105°C,Standard +105°C,标准品	-40~+105	6.3~500	0.1~22000	2000
	RC	+105°C,Miniature Specialdesigned for charger 小体积,特殊适用于快充领域	-40~+105	400~500	1~150	2000
铅笔型 Pen Type	BK	+105°C,Pen Type +105°C,铅笔型	-40~+105	160~450	22~330	2000
	BR	+105°C,Pen Type 铅笔型,长寿命	-40~+105	160~450	22~330	5000
	BT	+105°C,Pen Type 铅笔型,超长寿命	-40~+105	160~450	22~330	10000
高耐压 High Voltage	HV ^{NEW}	High Voltage For 750WV 超高电压,750WV 高浪涌对策品	-40~+105	550~750	1~150	2000
超小型 Low Profile	X5	+105°C,5mmL,Standard 5mm 高,+105°C	-40~+105	6.3~50	0.1~330	1000
	X7	+105°C,7mmL,Standard 7mm 高,+105°C	-40~+105	6.3~50	0.1~470	1000
	T7	+105°C,7mmL,Low ESR 7mm 高,低阻抗,长寿命	-40~+105	6.3~50	0.1~330	2000
	L7	+105°C,7mmL, Long Life 7mm 高,长寿命	-40~+105	6.3~50	0.1~470	5000
无极性 Non-Polar Type	NP	+105°C,Nonpolar +105°C,无极性	-40~+105	6.3~250	1~6800	2000
	NA	Standard,For Audio +105°C,标准品,音响电容	-40~+105	50/100	1~68	2000
特殊产品 Special Type	LK	Low leakage current +105°C,低漏电	-40~+105	6.3~100	0.47~2200	2000
	CF	Recharging And Discharging in Flash 闪光灯充放电用品	-25~+55	330/360	300~1500	5000Times

系列表 Series List

>>>大型铝电解电容器 Large Can Aluminum Electrolytic Capacitors

Type	Series	Features	Temperature (°C)	Voltage (V.DC)	Capacitance (μF)	Load Life (Hrs)
SNAP-IN 牛角型 	LP	Lug/Snap-in Terminal Type, Standard 插入/自立型, 标准品	-40~+85	10~550	68~82000	2000
	HP	Lug/Snap-in Terminal Type, Wide Temperature 插入/自立型, 宽温品	-40~+105	10~550	68~82000	2000
	GP	Lug/Snap-in Terminal Type, Long Life 插入/自立型, 长寿命	-40~+105	10~500	68~82000	5000
	FP	Lug/Snap-in Terminal Type Suited for Photo Flash 插入/自立型, 闪光灯充放电用	-25~+55	330/360	150~1500	5000Times
	DP ^{NEW}	Lug/Snap-in Terminal Type, Long Life 插入/自立型, 长寿命	-40~+105	10~500	68~82000	10000
	CP ^{NEW}	Lug/Snap-in Terminal Type, Long Life 插入/自立型, 超长寿命	-40~+105	10~500	68~82000	20000
SCREW 螺钉型 	SA	Screw Terminal Type Standard +85°C 螺钉型, 标准品, +85°C	-25~+85	350~550	1000~15000	2000
	SC	Screw Terminal Type Long life +85°C 螺钉型, 长寿命, +85°C	-25~+85	350~500	1000~15000	5000
	SD ^{NEW}	Screw Terminal Type Long life +85°C 螺钉型, 长寿命, +85°C	-25~+85	350~500	1000~15000	20000
	SK	Screw Terminal Type Standard +105°C 螺钉型, 标准型, +105°C	-25~+105	350~500	1000~15000	2000
	SR	Screw Terminal Type Long life +105°C, 螺钉型, 长寿命, +105°C	-25~+105	350~450	1000~15000	5000
	ST ^{NEW}	Screw Terminal Type High ripple current Long life +105°C, 螺钉型, 高纹波电流, 长寿命	-25~+105	350~450	1000~15000	5000