

系列	容值	料号	电压	安规认证	材质(温度特性)	封装	容量允差
TRX SMD-Y1.CAP	10PF/22PF 47PF/68PF	TMY1100J-AM/TMY1220J-AM TMY1470J-AM/TMY1680J-AM	400VAC 250VAC	CQC/KC UL/ENEC	SL (SL)	7854 7.8*5.4*2.38	J(±5%)
	100PF/220PF 330PF/470PF	TMY1101K-AM/TMY1221K-AM TMY1331K-AM/TMY1471K-AM	400VAC 250VAC	CQC/KC UL/ENEC	Y5P (B)	7854 7.8*5.4*2.38	K(±10%)
	470PF/680PF 1000PF/1500PF	TMY1471M-AM/TMY1681M-AM TMY1102M-AM/TMY1152M-AM	400VAC 250VAC	CQC/KC UL/ENEC	Y5U (E)	7854 7.8*5.4*2.38	M(±20%)
	2200PF	TMY1222M-AM	400VAC 250VAC	CQC/KC UL/ENEC	Y5V (F)	7854 7.8*5.4*2.38	M(±20%)
TRX SMD-Y1.CAP 高容系列	680PF/1000PF	TGY1681K-AM TGY1102K-AM	400VAC 250VAC	CQC/KC UL/ENEC	Y5P (B)	10596 10.5*9.6*2.58	K(±10%)
	2200PF/3300PF 4700PF	TGY1222M-AM TGY1332M-AM TGY1472M-AM	400VAC 250VAC	CQC/KC UL/ENEC	Y5U (E)	10596 10.5*9.6*2.58	M(±20%)
	10000PF	TGY1103M-AM	400VAC 250VAC	CQC/KC UL/ENEC	Y5V (F)	10596 10.5*9.6*2.58	M(±20%)
TL SMD-Y2.CAP	22PF/47PF	TBY2220KSL-AM TBY2470KSL-AM	300VAC 250VAC	CQC/KC UL/ENEC	SL (SL)	4335 4.3*3.5*2.2	K(±10%)
	68PF/100PF 220PF/330PF	TBY2680KB-AM/TBY2101KB-AM TBY2221KB-AM/TBY2331KB-AM	300VAC 250VAC	CQC/KC UL/ENEC	Y5P (B)	4335 4.3*3.5*2.2	K(±10%)
	470PF/680PF 1000PF	TBY2471ME-AM TBY2681ME-AM TBY2102ME-AM	300VAC 250VAC	CQC/KC UL/ENEC	Y5U (E)	4335 4.3*3.5*2.2	M(±20%)
	1500PF/2200PF	TBY2152MF-AM TBY2222MF-AM	300VAC 250VAC	CQC/KC UL/ENEC	Y5V (F)	4335 4.3*3.5*2.2	M(±20%)
TL SMD-Y2.CAP 高容系列	680PF/1000PF	TGY2681KB-AM TGY2102KB-AM	300VAC 250VAC	CQC/KC UL/ENEC	Y5P (B)	6056 6.0*5.6*2.2	K(±10%)
	2200PF/3300PF	TGY2222ME-AM TGY2332ME-AM	300VAC 250VAC	CQC/KC UL/ENEC	Y5U (E)	6056 6.0*5.6*2.2	M(±20%)
	4700PF	TGY2472MF-AM	300VAC 250VAC	CQC/KC UL/ENEC	Y5V (F)	6056 6.0*5.6*2.2	M(±20%)
SMD-DC.CAP TB系列	2PF-2200PF	参考规格书	1KV、2KV 3KV	/	SL (SL)、Y5P (B)、 Y5U (E)、Y5V (F)	4335 4.3*3.5*2.2	K(±10%) M(±20%)
SMD-DC.CAP TC系列	680PF-4700PF	参考规格书	1KV、2KV 3KV	/	Y5P (B)、Y5U (E)、 Y5V (F)	6056 6.0*5.6*2.2	K(±10%) M(±20%)
SMD-DC.CAP TD系列	680PF-10000PF	参考规格书	1KV、2KV 3KV	/	Y5P (B)、Y5U (E)、 Y5V (F)	10596 10.5*9.6*2.58	K(±10%) M(±20%)
TY DIP-Y1.CAP	100PF-4700PF	参考规格书	500VAC	CQC/KC/VDE UL/ENEC	Y5P (B)、Y5U (E) Y5V (F)	/	K(±10%) M(±20%)

备注1

具体参数以spec为准

备注2

其他问题请咨询联络TRX销售部门或代理商

备注3

高容量系列产品针对有更高容值要求、更稳定温度表现客户及应用开发

Tel : +86-755-29615180 Fax : +86-755-29971027

E-mail : anmu@anmutech.com